



Ultra-Portable Equipment for Voice & Data Testing



vMobile™ in Hand



vMobile™ Interfaces



Overview

vMobile™ is GL's new offering under its wide variety of [Voice and Data Quality Testing](#) tools. The vMobile™ is a handheld ultra-portable device that brings true mobility to voice and data quality testing for any mobile phone and any mobile radio, changing the way automated drive and walk testing is performed. The vMobile™ is simple to setup and conduct operate for running these tests in order to benchmark both mobile phone networks and mobile radio networks.

The [vMobile™ handheld device](#) supports fully automated audio testing for mobile phones (any phone, any carrier, any network) including Voice Quality using POLQA, Delay measurements, Audio Dropout analysis, and full call control with Call Fail and Call Drop metrics. All tests include GPS location for plotting results and events within Google Maps using the GL [WebViewer™](#). In addition, the vMobile™ device supports fully automated audio testing for mobile radios (including connectivity to any 4-wire Analog device). This allows remote testing of mobile radios with automated PTT (Push to Talk) along with Voice Quality and Delay measurements.

The vMobile™ can be hand-carried for walk and drive testing (includes GPS) as well as left in labs and can work directly with GL's [VQuad™ solution](#) for very flexible end-to-end testing. All functionality and configuration of the vMobile™ is provided using the remote web-based Console and Console App which is installed on any Android or iOS device. In essence, the vMobile™ is an expansion of GL's current VQuad™ Voice and Data testing solution.

The vMobile™ handheld portable hardware includes two Bluetooth® modules (connecting to two mobile phones simultaneously), a 4-wire analog port with PTT for connecting to any mobile radio or any analog headset interface, an embedded Wi-Fi module for communicating to the Central System, and an onboard GPS receiver. The user can easily select either Bluetooth or Analog mode. The embedded Wi-Fi supports remote operation along with remote audio analysis and sends all results/events to a Central Database, accessed through GL [WebViewer™](#) (web browser).

GL's [Indoor Tracking System \(ITS\)](#) functionality supports plotting voice quality results when GPS is not available (for instance indoors). The ITS allows viewing the results directly plotted on a user provided floorplan or map.

GL's [Voice Analysis Tool \(VAT™\)](#) application is used to analyze the audio content within any PCM audio files and generates a variety of audio metrics. VAT™ has a user-friendly interface to perform manual and automated analysis of multiple tests using a single PCM audio file received from the VQuad™, vMobile™, or any other applications.




818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A
(Web) www.gl.com - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) info@gl.com

Main Features

- Fully automated voice and data testing in any mobile network
- Automation includes remote operation of far-end vMobile™ or GL VQuad™ system
- Connect to any radio via wired headset
- Can operate either in Bluetooth mode or Analog mode (connect to any 4-wire Analog device including Mobile Radio with PTT)
- Automated mobile Voice Quality Testing using embedded Wi-Fi for connecting to Central system and supporting full remote configuration and operation
- Onboard battery with availability of small portable external battery providing up to 12 hours operation
- Handheld and portable including several remote options for operation and configuration
- Operation and Configuration supported via web-browser Console or Android/IOS Console app
- Drive and Walk Testing fully supported using any Mobile Phone (any carrier) or Mobile Radio
- Supports GPS along with GL's ITS for automated drive and walk testing
- Supports Voice Quality Testing using POLQA (ITU-P.863) and PESQ (ITU-P.862) algorithms
- Supports several audio metrics including Signal and Noise levels, power, frequency, and Audio Dropout analysis
- vMobile™ scripting supports all operations including conditional statements
- Bluetooth supports both Narrowband (NB, 8000 sampling) and Wideband (WB, 16000 sampling)
- Supports fully automated operation including voice and enabling PTT
- Analog PTT supports Narrowband (NB, 8000 sampling), Wideband (WB, 16000 sampling), and Super-Wideband (SWB, 48000 sampling)
- Measure One Way Delay, PTT Audio Connection Delay time, PTT Grant Tone Delay time on Radio networks
- Fully automated tests while sending events/results to Central System for analysis and Access (WebViewer™)
- Full Audio Analysis using GL VAT™ that supports One Way and Round Trip Delay measurements, Signal and Noise Levels, Speech Activity, Audio Dropout Analysis along with additional analytical functions
- Access all results via a web browser (GL WebViewer™) and view results on Google Maps. Generate custom reports

Operations and Controlling vMobile™



The vMobile™ Console application for Android/IOS devices can be used to monitor, configure, and operate vMobile™ units. In addition the app can be used to write vMobile™ scripts and upgrade vMobile™ units when necessary. Multiple vMobile™ units can be controlled from one vMobile™ app.

The vMobile™ Console, running on the central system, has the same functionality as the vMobile™ app. In addition, the Console and Console app can access Bluetooth and Error logs from the individual vMobile™ units. Configuration settings include connections to the Central System and Console, Wi-Fi Network connection, Bluetooth connection for the mobile test phones, sample rate, mode of operation (Bluetooth or Analog PTT), all configured from the Console and Console app.

vMobile™ can also work with VQuad™ solution (vMobile™ in the field and VQuad™ with Dual UTA HD or VQuad™ Probe in the lab or static location). Both the systems connect to Central System and WebViewer™. Central Database with WebViewer™ allows access to all events and results while also plotting results on Google Maps.


Automated Call Control via Bluetooth®



The Bluetooth® modules on vMobile™ connect to two independent mobile phones to perform automated voice quality analysis along with delay measurements on Bluetooth® enabled mobile devices.

- Mobile (3G, VoLTE, VoWi-Fi, VoFemto, 5G) network with both NB and WB voice
- Supports any Mobile phone, any Carrier and any Network
- Voice Quality Analysis using POLQA algorithm of recorded voice files, supporting legacy as well as 5G and VoLTE networks
- Bluetooth® connectivity also supports RSSI, Battery level functions, and Network identity


Automated Analog (4-Wire) Testing



The vMobile™ can interface with mobile phones via wireless Bluetooth or mobile radios via wired headset for voice quality testing. When connected to a mobile radio, fully automated PTT operation is available within the vMobile™ automated scripting. In addition, the vMobile™ 4-wire analog interface replaces any analog headset for any device.

- Connect to any mobile radio as an analog headset or replace an analog headset to the device
- Connect to any mobile phone via wireless Bluetooth headset
- Fully automated testing including control of device and performing voice quality analysis
- Supports GPS along with GL's Indoor Tracking System (ITS) for automated drive and walk testing

Results in WebViewer™ - From Drive Test



- Drive testing any Wireless phone or mobile radio with real-time GPS mapping using embedded vMobile™ GPS receiver
- GPS used for location and One Way Delay accurate timing
- All vMobile™ events and results include GPS location (latitude and longitude)
- GPS information is automatically sent to central database and accessed via Google Maps feature in [WebViewer™](#)

Buyer's Guide

Item No	Product Description
VQT291	vMobile™
VQT008	Voice Analysis Tool (VAT™)
VQT600	VQuad™ NetTest Data Server Solution
VQT601	Mobile Device Controller (MDC) Software
VQT611	Target Data Server (1 Gbps)

Item No	Related Hardware
VQT204	GPS for Dual UTA
VQT251	Dual UTA HD Next generation Dual UTA with FXO Wideband support
VQT252	Dual UTA HD – Bluetooth Option
VQT280	VQuad™ Probe HD (with Dual UTA HD)

Item No	Related Software
VQT010	VQuad™ Software (Stand Alone)
VQT002	Voice Quality Testing (PESQ only)
VQT006	Voice Quality Testing (POLQA)
VQT007	VQT POLQA v3, server license for 20 nodes
VQT014	Voice Quality Testing (VQT) POLQA Auto™
VQT014U	Upgrade from VQT POLQA to VQT POLQA Auto™
VQT040	Webviewer™

For more information, refer to [vMobile™ – Ultra-Portable Equipment for Voice & Data Testing](#) webpage